

RUST'S WORST ENEMY

**POWERFUL RUST & CORROSION PROTECTION
EXCELLENT VEHICLE UNDERCOATING
SUPERIOR LUBRICANT • LONG-TERM PENETRANT**



FLUID FILM®



"WOOL WAX FORMULA"

**ENVIRONMENTALLY FRIENDLIER
SOLVENT FREE • NON-TOXIC**

**AUTO • TRUCK • FARM • HOME • MARINE • FORESTRY • MINING • INDUSTRIAL • RVs
BUSES • TRAILERS • CHAINS • ATVs • AIRCRAFT • MILITARY • SALT TRUCKS • CABLES
BATTERY TERMINALS • TOOLS • FERTILIZER SPREADER • ELECTRICAL CONNECTORS**

THE MOST UNIVERSAL PRODUCT YOU WILL EVER USE!!

- NOT WATER SOLUBLE
- REPELS & RESISTS WATER WASHOUT
- WILL NOT DRY OUT OR EVAPORATE
- APPLY OVER DRY OR DAMP SURFACES
- REDUCES STRESS CORROSION

- PREVENTS ICE & SNOW FROM BUILDING UP ON MOVING PARTS
- WORKS IN SUB-ZERO WEATHER -46°C (-50°F) TO 177°C (350°F)
- NON-CONDUCTOR OF ELECTRICITY
- WILL NOT CAUSE STATIC ELECTRICITY
- SOLVENT, TEFLON & SILICONE FREE

NATURE GIVEN MATERIAL

FLUID FILM UTILIZES THE UNIQUE MOLECULAR ACTION DERIVED FROM WOOL-WAX, A NATURE GIVEN MATERIAL (Lanolin) & other corrosion inhibiting ingredients. One of the best lubricants & corrosion control agents found in nature today. In use for over 60 years in the Highly Corrosive Marine Environments of ships & off-shore drilling rigs.

PROVIDES LONG-TERM PROTECTION FOR ALL YOUR TOOLS & EQUIPMENT PROTECTIVE PROPERTIES START WORKING IMMEDIATELY

FLUID FILM - developed & perfected as an unparalleled Rust & Corrosion Control System. Non-drying properties for Superior Lubrication & is a Long Term Penetrant. Once in place, stays put, forming a continuous, durable, ALWAYS ACTIVE protective barrier. Will not harm most paint or plastic surfaces. Will not harm oil resistant seals. Take care when applying near rubber. Overspray must be wiped with a clean, dry cloth as it may cause swelling. Repels & resists water washout. Displaces moisture. Excellent waterproofing with "NO DRIP" bonding properties. FLUID FILM penetrates right through rust, stopping all metal deterioration on contact. Migrates to inaccessible areas by capillary action. Impregnates the pores of exposed metal, keeping moisture & oxygen out. Certified Salt Spray Test - 1800 Hrs. U.S. Navy & 10 Military GSA National Stock Numbers (NSN).

TERMINATES BOTH NATURAL & INDUSTRIAL ATMOSPHERIC CORROSION

Eliminates the destructive corrosive effects of harsh minerals & chemicals such as salt, salt air, brine solution, acid, calcium, sodium chloride, fertilizers, herbicides & pesticides. FLUID FILM prevents steel from rusting; aluminum, magnesium, copper, tin, bronze & zinc from oxidizing; chrome & brass from pitting.

VEHICLE UNDERCOATING APPLICATION INSTRUCTIONS

SHAKE WELL BEFORE USING. (Apply Sparingly) Apply FLUID FILM "NAS" by brush, roller, dipping or pressurized sprayer at 60 to 80 psi, (at the sprayer) with a spray nozzle orifice of 40-50 thou. KEEP CONTAINER TIGHTLY CLOSED. **FLUID FILM UNDERCOATING:** Give the vehicle's undercarriage a blast of water to clean off any excess dirt & let the heavy water drip off for 5 minutes. Apply to the panels and doors as normal. Apply FLUID FILM right over the damp metal. If dripping occurs then you are over-applying the product. If previously undercoated, please check for product compatibility.

**Aerosol (AS): # 1450 - 145 g, # 3300 - 333 g, Bulk (NAS): # 3700 - 3.78 L Can,
4300 - 18.9 L Pail, # 4500 - 208 L Drum, # 5207 - Brush Top Can - 237 ml
All above are Canadian Food Inspection Agency Approved (CFIA # N184)**

